



JJ-166TL

(A 2155)





Front View

Rear View

- A1 = Triangle Safety lock
- A2 = HDD power & access LED
- A3 = HDD LED Switch (enable/disable)
- A4 = 12V FAN 2pin Power output jumper
- A5 = 15pin power connector x 1
- A6 = SATA 7pin data connector x 1

| LED | | A1 | |
|-------|--------|------------|-------------|
| State | HDD in | HDD Access | A3 turn OFF |
| Color | Blue | Purple | Blue |
| Blink | х | 0 | х |

[*When A3 switch is turned to OFF position, the HDD accessing function is disable. In this case, the front LED is displayed

in solid blue only and that means it is with the power ON function only but without blinking accessing signal]



• Material: Aluminum Frame & bezel

Interface: Support SATA-I, II, III & SAS I, II

Transfer rate: Upto 6Gbps

Connector: 15pin SATA-power connector x 1 & 7pin data signal connector x 1

Black aluminum-body with Black panel

Trayless Design

 Triangle metal key-lock safeguards the hard disk in the correct position preventing it from bouncing out while HDD is in operation.

Hot swap in / out

1*5.25Bay for 1*3.5"SATA or SAS Hard drive

HDD LED functioning ON/OFF Switch

• Dim: 175(L) * 146(W) * 42(H) mm

Weight: 0.4 kg

Color: black